


Benefits

- Molded plastic hook is available in a range of resins (nylon, polyester, vinyl, polyethylene, polypropylene) to suit your particular application
- Molded hook shapes are engineered for superior performance with VELCRO® Brand woven and knit loops
- Most VELCRO® Brand HTH products are available wide and can also be converted into die-cut shapes and cut or scored pieces
- Variety of backings available including sewable scrims, weldable and heat sealable coatings, and pressure sensitive adhesives



THE VELCRO COMPANIES ARE WORLDWIDE LEADERS IN FASTENING SYSTEMS OFFERING A WIDE RANGE OF SOLUTIONS FROM STANDARD HOOK AND LOOP TO COMPLETE FINISHED PRODUCTS.

50 YEARS OF EXPERIENCE: WE ARE PROUD OF OUR HERITAGE IN INNOVATION, HAVING OVER 300 ACTIVE PATENTS TO OFFER BETTER SOLUTIONS TO SATISFY OUR CUSTOMERS' NEEDS.



North American Headquarters

United States

Velcro USA Inc.
406 Brown Avenue
Manchester, NH 03103
Tel: (800) 225 0180
Fax: (800) 835 2761
marketing@velcro.com
www.velcro.com

Canada

Velcro Canada Inc.
114 East Drive
Brampton, Ontario
Canada L6T 1C1
Tel: (905) 791 1630
Fax: (905) 791 5329
canada@velcro.com
www.velcro.ca

Mexico

Velcro de Mexico, S.A. de C.V.
Ave. Industria No. 102 Nave IV-A
Col. Los Reyes Pueblo
Tlalnepantla de Baz
Edo. De Mexico C.P. 54090
Tel: (+52) 55 5005 3300
Fax: (+52) 55 5384 5413
ventasmx@velcro.com
www.velcrodemexico.com

WORLDWIDE LOCATIONS



VELCRO® and other marks are owned by Velcro Industries B.V. © 2011.


VELCRO® Brand

High Technology Hook



MOLDED HOOK FASTENERS OFFERING A RANGE OF PERFORMANCE CHARACTERISTICS

VELCRO® Brand HTH provides an optimal balance of performance and comfort in this knee brace



High Technology Hook

Applications



Choose the right hook for your needs...

We offer countless hook style and resin combinations to meet a wide range of applications. Below are our most popular hooks. Please contact us for additional details on our full product line.

Hook	Style	Resin	Benefits
705	15	Nylon	Ideal for applications using adhesives
704	15	Polyester	UV and chemical resistant
711	15	Polyethylene	Economical
745	15	Nylon	For sew-on applications
719	15	Nylon	Uni-directional hook for applications requiring high shear
805	22	Nylon	Ideal for applications using adhesives
811	22	Polyethylene	Economical
845	22	Nylon	For sew-on applications
848	22	Vinyl	RF weldable

Hook	Style	Resin	Benefits
886	22	Nylon	For mold-in applications; Knit 3200 scrim back
810	22	Nylon	RF weldable
757	24	Nylon	For heavy duty applications with little to no cycling
752	24	Polypropylene	For heavy duty and outdoor applications; available in silver only
833	29	Nylon	Very low profile
830	29	Polypropylene	Very low profile
841	99	Nylon	Sewable; nylon scrim back
744	99	Vinyl	RF Weldable
847	108	Polypropylene	Soft, flexible, disposable

Hook Styles



15

- Designed for high profile woven and knit loops
- 750 hooks per square inch
- Hook height: 0.035 inches
- Standard hooks: 705, 704, 711, 745



22

- Designed for low profile knit loops
- 900 hooks per square inch
- Hook height: 0.028 inches
- Standard hooks: 805, 811, 845



24

- Designed for high profile woven and knit loops
- 130 hooks per square inch
- Hook height: 0.097 inches
- Standard hooks: 757, 752



29

- Designed for low profile knit and nonwoven loops
- 1700 hooks per square inch
- Hook height: 0.02 inches
- Standard hooks: 833, 830



99

- Designed for low to medium profile woven and knit loops
- 375 hooks per square inch
- Hook height: 0.025 inches
- Standard hooks: 841



108

- Designed for low profile knit and nonwoven loops
- 916 hooks per square inch
- Hook height: 0.015 inches
- Standard hooks: 847

Ask us about the VELCRO® Brand solutions for...

Medical & Orthopedics

- VELCRO® Brand Laminates
- VELCRO® Brand EVAPTEX™ Fabric
- VELCRO® Brand Double-Faced Loops

Packaging & Bundling

- VELCRO® Brand Bundle Ties
- VELCRO® Brand Easy Coins
- VELCRO® Brand PRESS-LOK™

Displays & Exhibits

- VELCRO® Brand ONE-WRAP®
- VELCRO® Brand Qwik Ties
- VELCRO® Brand Woven Fasteners

